



Manufacture Hdw Locations:

- Amweld
- Steelcraft
- Ceco
- Republic
- Deansteel
- Curries
- Other _____

Hinge Prep Codes

- 345 = 3 ea 4 1/2" hinge preps
- 345H = 3 ea 4 1/2" HW hinge preps
- 445 = 4 ea 4 1/2" hinge preps
- 350 = 3 ea 5" hinge preps
- E### = Elec. prefix for hinge code
- FMCH = Full mort. cont. hinge, blank hinge stile under sized door leaf to suit
- FSCH = Full surface cont. hinge, blank hinge stile
- PVT = Pivot prep (see template)

Nominal Size		Thickness: <input type="checkbox"/> 1-3/4" <input type="checkbox"/> Other	
Net Size			
Hinge Prep:			
Lock Prep:			
Active Leaf -			
Inactive Leaf -			
Hollow Metal		Wood	
Core: <input type="checkbox"/> Steelstiffened <input type="checkbox"/> Honeycomb		<input type="checkbox"/> Particalboard <input type="checkbox"/> Stave Lumber	
<input type="checkbox"/> Polystyrene <input type="checkbox"/> Polyurethane		<input type="checkbox"/> Mineral <input type="checkbox"/> SCL	
Face: <input type="checkbox"/> 18 ga <input type="checkbox"/> 16 ga		<input type="checkbox"/> Rotary Cut <input type="checkbox"/> Plain Sliced	
Material: <input type="checkbox"/> A60 <input type="checkbox"/> Stainless		<input type="checkbox"/> White Birch <input type="checkbox"/> Natural Birch	
Edge: <input type="checkbox"/> Lock Seam (Standard)		<input type="checkbox"/> Red Oak <input type="checkbox"/> White Maple	
<input type="checkbox"/> Seamless Bondo		<input type="checkbox"/> Hardboard <input type="checkbox"/> Plastic Laminate	
<input type="checkbox"/> Seamless Welded		Finish: <input type="checkbox"/> Factory Defined Stain	
Topcap: <input type="checkbox"/> Inverted		<input type="checkbox"/> Match Custom Color	
<input type="checkbox"/> Flush <input type="checkbox"/> Sealed		<input type="checkbox"/> Raw <input type="checkbox"/> Clear <input type="checkbox"/> Primed	

Lock Prep Codes

161 = Standard 2 1/8" face bore x 2 3/4" B.S.
 D/L1 = Deadlock 1 1/2" face bore x 2 3/4" B.S.
 D/L2 = Deadlock 2 1/8" face bore x 2 3/4" B.S.
 MDL = Mortised deadlock
 RP = Rim panic (see template if function holes req'd)
 SVR = Surface vertical rod panic device
 CVR = Concealed vert rod panic (see template)
 MP = Mortised Panic - 8" high edge pocket
 86 = Full mortised lock - 8" high edgve pocket
 INA = ASA strike and extension rod flushbolts
 INW = ASA strike and wood door flushbolts

Blank = No lock or panic prep

Lite - Louver

Cutout Size _____

Top of Door to Cutout Top _____

Btm of Door to Cutout Btm _____

Lock Stile _____

Lite/Louver Model# _____

Glass Type _____



Instructions: _____

Qty.	Handing	UL	Mark #

eighty-nineA, LLC 6745 S. Harl Ave. Suite 102 Tempe, Az. 85283 480-838-1620 phone 480-838-1618 fax		Paired Door Order Form			
Company Name:	P.O. #:	Job Name:	Page:	Of:	