



**anchors**

- 5 = Welded steel stud 'Z' anchor (Inset)
- 5F = Welded steel stud 'Z' anchor (Flush)
- 7 = Snap in combo stud
- 7A = 2 pc. adjustable combo stud
- 8 = Punch & Dimple (P&D)
- 8E = #8 w/ Exp. bolts (Masonry)
- 8W = #8 w/ Wood lag screws
- 9 = Wire masonry anchors
- 12 = wood stud welded straps
- 14 = Compression w/ base straps
- 15 = Compression w/ base dimples
- SCR = Screws on face & covered by trim

**Profile Codes**

PFHM = Prefinished HM

- D = Dble Rabbet      DW = Drywall Returns
- S = Single Rabbet    C = Cased Open
- ##L = Lead Suffix

\* - Draw in mullions as needed.

Overall Size:	
Inside (Glass Opening Size):	
Gauge: <input type="checkbox"/> 16 <input type="checkbox"/> 14 <input type="checkbox"/> 12	<input type="checkbox"/> 20 <input type="checkbox"/> 18 Prefinished HM
<input type="checkbox"/> BR <input type="checkbox"/> BK <input type="checkbox"/> WH <input type="checkbox"/> AL	
Material: <input type="checkbox"/> A60 <input type="checkbox"/> Stainless <input type="checkbox"/> Other	
Anchors:	
Material: <input type="checkbox"/> A60 <input type="checkbox"/> Stainless	<input type="checkbox"/> Spot Prime (Standard) <input type="checkbox"/> Fully Prime (Extra)
Label: <input type="checkbox"/> 20 min. <input type="checkbox"/> 45 min. <input type="checkbox"/> 60 min. w/ firelite	
<input type="checkbox"/> Knock-down (Installed K.D.)	<input type="checkbox"/> Knock-down (Welded by others) <input type="checkbox"/> Welded <input type="checkbox"/> Full Throat Welded (Extra)

Jamb Depth: _____	Profile Code: _____
<input type="checkbox"/> Unequal Rabbet	<input type="checkbox"/> Equal Rabbet

<b>Glazing Bead Notes</b>	
<input type="checkbox"/> 5/8"	<input type="checkbox"/> 3/4" Installed
<input type="checkbox"/> Loose	- Pocket Depth _____
	- Wide Side <input type="checkbox"/>
	- Narrow Side <input type="checkbox"/>

Instructions: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Qty.:	Mark #:

<p><b>eightynineA, llc</b>          6745 S. Harl Ave. Suite 102          Tempe, Az. 85283          480-838-1620 phone          480-838-1618 fax</p>	<h1>Borrowed Lite Order Form</h1>			
Company Name:	P.O. #:	Job Name:	Page:	Of: