



### PRODUCT DESCRIPTION

Mineral core fire doors intended for use where 90 min. fire barriers are required. W.H.I. label (*Warnock-Hersey, Inc.*).

All doors meet or exceed current industry standards.

- Current WDMA I.S. 1A
- W.I.C. Section 20
- A.W.I. Section 1300 when specified

### ITEM SPECIFICATIONS

<b>Maximum Size</b>	3'-0" x 10'-0" single swing 4'-0" x 9'-0" single swing 8'-0" x 8'-0" double egress pairs
<b>Thickness</b>	1 <sup>3</sup> / <sub>4</sub> " only
<b>Stiles</b>	Latch stile <sup>3</sup> / <sub>4</sub> " "Firestop" Hinge stile 1" "Firestop" Hardwood edgebands as specified
<b>Rails/Lock Blocks</b>	Top Rail <sup>3</sup> / <sub>4</sub> " "Firestop" minimum Bottom Rail 1 <sup>3</sup> / <sub>4</sub> " "Firestop"
<b>Core</b>	Incombustible non-asbestos mineral core engineered to meet labeling requirements
<b>Adhesives</b>	Type 2. Type 1 available.
<b>Faces</b>	All commercially available hardwood species, medium density overlay, and high -pressure plastic laminates
<b>Vision Panels &amp; Louvers</b>	See W.H.I. specifications
<b>Prefitting</b>	May be prefit to net sizes as specified
<b>Machining</b>	May be factory machined for hardware as specified
<b>Warranty</b>	Up to life of the original installation. See full Haley Brothers Warranty for specific coverages
<b>Short Form Specification</b>	Doors shall be "90 Minute Label," manufactured according to the specifications shown in the Haley catalog

NOTE: All dimensions are before trimming. "Firestop" is a product of Georgia-Pacific Corporation.